

1 **UK-TYPE EXAMINATION CERTIFICATE**

2 **Equipment or Protective System Intended for use in Potentially Explosive Atmospheres**
UKSI 2016:1107 (as amended) – Schedule 3A, Part 1

3 UK-Type Examination Certificate Number: **BAS21UKEX0429X**
4 Product: **Type F Float Switches**
5 Manufacturer: **Cynergy3 Components Ltd**
6 Address: **7 Cobham Road, Ferndown Industrial Estate, Wimborne, Dorset, BH21 7PE**

7 This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

8 SGS Baseefa, Approved Body number 1180, in accordance with Regulation 43 of the Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016, UKSI 2016:1107 (as amended), certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Schedule 1 of the Regulations.

The examination and test results are recorded in confidential Report No. **18(C)0309**

9 Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0:2018 EN 60079-1:2014 EN 60079-26:2015 EN 60079-31:2014

except in respect of those requirements listed at item 18 of the Schedule.

10 If the sign “X” is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.

11 This UK-TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified product. Further requirements of the Regulations apply to the manufacturing process and supply of this product. These are not covered by this certificate.

12 The marking of the product shall include the following :

⊕ II 1/2GD Ex db IIC T4 Ga/Gb Ex tb IIC T110°C Db

SGS Baseefa Customer Reference No. **7692**

Project File No. **18/0309**

This document is issued by the Company subject to its General Conditions for Certification Services accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and the Supplementary Terms and Conditions accessible at <http://www.sgs.com/SGSBaseefa/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. It does not necessarily indicate that the equipment may be used in particular industries or circumstances. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, schedule included, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Baseefa Limited


Rockhead Business Park, Staden Lane,
Buxton, Derbyshire SK17 9RZ

Telephone +44 (0) 1298 766600 Fax +44 (0) 1298 766601
e-mail baseefa@sgs.com web site www.sgs.co.uk/sgsbaseefa

Registered in England No. 4305578.

Registered address: Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN




R S SINCLAIR
TECHNICAL MANAGER
On behalf of SGS Baseefa
Limited

13

Schedule

14

Certificate Number BAS21UKEX0429X

15 Description of Product

The Type F Float Switch comprises a cylindrical enclosure with a spigoted cover attached by four A4-80 stainless steel screws. It used the flameproof protection concept. The enclosure and cover can be cast or machined from brass or stainless steel.

The base which may be threaded or provided with a welding spigot for attachment to the process media, is drilled to house a stem tube containing up to four hermetically sealed reed switches or thermal switches, or a combination of both.

The switches are rated up to 250V a.c. or d.c. 3A. The stem tube is fully potted and the reed switches are actuated by an external float containing a magnet. The enclosure contains terminals, and an internal earth facility.

16 Report Number

18(C)0309

17 Specific Conditions of Use

1. The plastic material of the floats is not static dissipative so is a potential electrostatic discharge risk. This part of the equipment should be cleaned only with a damp cloth and should not be mounted in high airflow dust laden atmospheres.
2. The selected cable entries (whether gland or conduit) shall be suitably certified and shall be installed so as to maintain the enclosure's ingress protection of IP6X.
3. The cable and cable entries shall be capable of operating in an ambient temperature range of -50°C to +100°C.

18 Essential Health and Safety Requirements

In addition to the Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9, the following are considered relevant to this product, and conformity is demonstrated in the report:

Clause	Subject
1.2.3	Enclosed structures to prevent leaks
1.2.7	LVD type requirements
1.4.1	External effects
1.4.2	Aggressive substances, etc.

19 Drawings and Documents

Number	Sheet	Issue	Date	Description
2000	3	AA	21/07/17	Flameproof float switch, displacer, temperature & mechanically linked head, stem and switch assembly design.

This drawing is associated with SGS21ATEX0116X.

For all drawings see SGS21ATEX0116X.